METAWOLF SOLAR


BlackLux Clear

MW-SP435-8B108DFT-10

N-Type HJT
Clear Mesh Double Glass

435W Power

22.28% Efficiency



30 Yrs PRODUCT WARRANTY

30 Yrs LINEAR POWER WARRANTY

Exceeds the requirements of hail resistance 4 (HW4) confirmed by TÜV Süd

2 X2 mm Glass Front and Back

· Better hail resistance with 45 mm ice ball at 110 km/h
vs IEC Standard: 25 mm ice ball at 83 km/h

· Higher snow load and wind load resistance with tested up to 6336 pa (Front) and 5530 pa (Rear)
vs IEC Standard: 5400 pa (Front) and 2400 pa (Rear)

HJT Technology

Combining gettering process and double-sided µc-Si to maximize cell efficiency and module power.

Butyl Edge Sealing

· Zero water ingress → zero corrosion
· Superb durability for a longer lifespan

Up to 95% Bifaciality

vs PERC: 70%.
vs TOPCon: 80%

Electrical Characteristics (STC*)

Module Type	MW-SP435-8B108DFT-10
Maximum Power (Pmax)	435W
Module Efficiency	22.28%
Maximum Power Voltage (Vmp)	34.86V
Maximum Power Current (Imp)	12.48A
Open Circuit Voltage (Voc)	41.64V
Short Circuit Current (Isc)	13.00A
Operating Temperature	-40°C to + 85 °C
Maximum System Voltage	DC1500V(IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0 ~ +5W
Bifaciality	90% ± 5%

*STC: Irradiance 1000 W/m², cell temperature 25°C, AM=1.5. Tolerance of Pmax is within+/- 3%.


BSTC**

Module Type	MW-SP435-8B108DFT-10
Maximum Power (Pmax)	485W
Maximum Power Voltage (Vmp)	34.86V
Maximum Power Current (Imp)	13.92A
Open Circuit Voltage (Voc)	41.64V
Short Circuit Current (Isc)	14.49A

**BSTC: Front side irradiation 1000W/m²,back side reflection irradiation 135W/m²,AM=1.5, ambient temperature 25 °C.

Engineering Drawings

Unit: mm



Mechanical Characteristics

Cell Type	HJT Mono 182×91.75mm
Cell Connection	108 (6×18)
Module Dimension	1722×1134×30 mm
Weight	26 kg
Junction Box	IP68
Output Cable	4mm², 1200mm in length, length can be customized / UV resistant
Connectors Type	MC4 original
Frame	Anodised aluminum alloy (Black)
Front Load	5400Pa
Rear Load	2400Pa
Glass Thickness	Double glass, 2.0mm


Temperature Characteristics

Nominal Operating Cell Temp. (NOCT)	44°C±2°C
Temperature Coefficient of Pmax	-0.26%/°C
Temperature Coefficient of Voc	-0.24%/°C
Temperature Coefficient of Isc	0.04%/°C

Safety & Warranty

Safety Class	Class II
Product Warranty	30 yrs Workmanship (For Rooftop Installation)*
Performance Warranty	30 yrs Linear Warranty*

*Less than 1% attenuation in the 1st year, the annual attenuation from the 2nd year is no more than 0.375%, and the power is no less than 88% until the 30th year.



*Refer to Metawolf Solar standard warranty for details.

Shipping Configurations

Container Size	40'HQ
Pallets Per Container	26
Modules Per Pallet (pcs)	36
Modules Per Container (pcs)	936

* The module recycling should be carried out by the professional institutions at the end of module life cycle
* Copyright@2023 Specifications are subject to change without further notification

Meta Wolf Solar GmbH - Gießener Str. 42 - DE 35410 - Hungen - Tel. +49 6402 / 89 89 050 - Mail. info@metawolf-solar.com